



EXCEL INDUSTRY CO. LLC

1.1 CBM

GALVANIZED BIN

PLASTIC FLAT LID,

SQUARE BODY



FEATURES

Body Standard 1.4mm case, 1.5mm bottom, covered drain hole is located on the bottom.

Loading Capacity 440 Kgs.

Wheel Loading Capacity 205 Kgs each

Handles on both sides of the bin.

Lid made from recycled plastic material (Duraflex) with optional colours.

Surface zinc coating according to EN ISO 1461

Wheels 4 rubber swivel castor wheels \varnothing 200mm (2 wheels fitted with brake)

Comb bar /Lifting Trunnion Integrated comb bar with chip nest and lifting trunnions (bolted) as per BS EN 840-2

Welding All welds to be 3mm stitch/full welding.

Own weight 110 Kgs.

TECHNICAL SPECIFICATION

Capacity	1.1 m ³
Width	1035 mm
Length	1420mm
Height	1300 mm
Material	Hot-rolled sheet as per BS EN 10029
Finish	Hot-dip galvanized as per BS EN ISP 1461 / ASTN A123
Approx. Wt	110 Kgs

ACCESSORIES

Handles on both sides of the bin.

Lid made from recycled plastic material (Duraflex) with optional colours.

4 rubber swivel castor wheels \varnothing 200mm (2 wheels fitted with brake)



+971 6 7430 320
+971 6 5262 200



enquiry@excel-uae.com
www.excel-uae.com



P.O. Box 1196,
Ajman, UAE.